



Your value-added manufacturer with the services and response of a just-in-time distributor.

WORLD CLASS
WIRE & CABLE, INC.

Voice, Data, and Premise Wire *Non-Shielded/Multiple Conductor*

UL Type CMR, CL3R, 75C

AWG Size	NO. of Conds.	Conductor Stranding	Nominal Insulation	Nominal Jacket	Nominal Diameter	Approx. Lbs./Mft.
22	2	7BC	0.008	0.015	0.12	9
22	3	7BC	0.008	0.015	0.14	13
22	4	7BC	0.008	0.015	0.16	17
22	6	7BC	0.008	0.015	0.17	22
22	12	7BC	0.008	0.015	0.22	42
22	12	7BC	0.008	0.015	0.22	42
20	2	7BC	0.008	0.015	0.13	11
20	3	7BC	0.008	0.015	0.13	18
20	4	7BC	0.008	0.015	0.14	22
18	2	7BC	0.009	0.015	0.16	18
18	3	7BC	0.009	0.015	0.17	24
18	4	7BC	0.009	0.015	0.18	31
18	6	7BC	0.009	0.015	0.23	46
18	8	7BC	0.009	0.015	0.25	59
18	12	7BC	0.009	0.015	0.29	86
16	2	19BC	0.009	0.015	0.18	26
16	3	19BC	0.009	0.015	0.19	35
16	4	19BC	0.009	0.015	0.21	47
14	2	19BC	0.013	0.015	0.22	41
14	3	19BC	0.013	0.015	0.24	55
14	4	19BC	0.013	0.015	0.26	72
12	2	19BC	0.013	0.015	0.26	57

- Can be used in remote control signaling and power-limited circuit applications where protection from electrostatic interference is not required, for security, intercom, public address, sound, and audio systems.
- Conductors are soft bare annealed copper per ASTM B-3.
- Insulation is semi-rigid Polyvinylchloride (PVC)
- Jacket is gray PVC with a ripcord applied longitudinally under the jacket to facilitate stripping.
- Flame Test- UL1666 flame test

- Additional Standards:

22AWG-16AWG: UL standard 13, NEC Article 725 Type CL3R and UL Standard 444, NEC Article 800 Type CMR
14AWG: UL standard 13, NEC Article 725 Type CL3R

Corporate Headquarters & Main Warehouse

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • WWW.WCWC.COM